

Wilson 400 Plenum Cable

SKU: 952001

FEATURES

- UL rated CMP/FT6
- Flexible conductor enables tight bend radius
- Low-loss coaxial cable for wireless applications
- For indoor plenum use (dropped ceilings and raised floors)
- Meets all code requirements for installation in plenum air handling spaces



952001 Wilson 400 Plenum Cable shown

Specifications

Wilson 400 Plenum Cable

Dielectric Insulation	FEP
Center Conductor Material	Copper Clad Aluminum
Center Conductor Diameter	.107 in
Center Conductor Construction	Solid
Nominal Core O.D.	0.320 in
Nominal O.D.	0.40 in
VOP	76%
Shield %	100% foil 90% braid
Nominal Capacitance (pF/ft)	26.5
Attenuation	dB/100ft
Loss @ 50 MHz	0.994 dB

(Con't Wilson 400 Plenum Cable)

Loss @ 100 MHz	1.351 dB
Loss @ 400 MHz	2.94 dB
Loss @ 900 MHz	4.762 dB
Loss @ 1000 MHz	5.065 dB
Loss @ 1800 MHz	7.232 dB
Loss @ 2500 MHz	8.839 dB
Jacket Color	Orange Jacket
Mfg. Warranty	5 Years
Jacket Material	FRPVC
Rating	UL/CMP
Braid Material	Tinned Copper

Support



2 Year Warranty

Email: support@wilsonelectronics.com

Website: <http://support.weboost.com>

Phone: +1 866 294 1660
Monday to Saturday